

# Steel Electric Powered Floor Crane 2500 Lb. Retracted Capacity Yellow

## MODEL EPFC-25

Overhead Lifting / Electric Powered Floor Cranes



### PRODUCT OVERVIEW

The fully powered electric floor crane has an easy and quick operation. The unit raises and lowers loads with the push of a button and can maneuver loads in warehouses and trailers. The heavy duty rigid hook with safety latch provides long service. The high-torque DC drive and lift motors handle heavy-duty jobs. Floor crane includes integral battery charger, battery level gauge, and emergency battery disconnect. The truck rolls smoothly on poly-on-steel, steer and load wheels. Ergonomic handle features easy to operate throttle with infinite adjustment of forward and reverse speeds, controlled lift/lower controls, adjustable length legs, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergen...

### KEY FEATURES

- Fully-powered floor crane makes movement of material quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction with infinite speeds

### CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**865 lbs**

ASSEMBLED SIZE  
**30" W x 79.5" L x 66.375" H**

SHIP WEIGHT  
**1006 lbs**

PACKAGE 1 SIZE  
**47" W x 89" D x 69" H**

COLOR / FINISH  
**Yellow**

FREIGHT TYPE  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                               |               |
|-----------------------------------------------|---------------|
| Uniform Capacity Retracted (lb.)              | 2,500         |
| Uniform Capacity Boom Half-Way Extended (lb.) | 1300          |
| Uniform Capacity Boom Fully Extended (lb.)    | 600           |
| Width Between Legs/Wheels - Retracted (in.)   | 23            |
| Width Between Legs/Wheels - Extended (in.)    | 28            |
| Manual Extension Holes (qty.)                 | 3             |
| Space Between Holes (in.)                     | 8             |
| Maximum Height - Crane Extended (in.)         | 110           |
| Max. Length - Legs Extended (in.)             | 103-1/8       |
| Lift Range - Retracted (in.)                  | 44-1/4        |
| Lift Range - Extended (in.)                   | 94            |
| Drive Motor                                   | DC24V / 0.7KW |
| Lift Motor                                    | DC24V / 2KW   |
| Battery (quantity)                            | 2             |
| Battery Type                                  | 12V           |
| Battery Charger                               | 24V / 12 AMP  |
| Battery Charger Power Cord                    | 115V AC       |
| Minimum Service Per Charge (hrs.)             | 8             |
| Lift Speed w/o Load (seconds)                 | 0.7           |
| Lift Speed w/ Load (seconds)                  | 0.5           |
| Battery Charge Time (hrs.)                    | 8             |
| Charger Cord Length (in.)                     | 62            |
| Charger Plug Type                             | 3 Prong       |
| Specifications                                | ANSI Z535     |
| Hook Material                                 | Steel         |
| Hook Opening (in.)                            | 1-1/4         |
| Wheel Material                                | Poly          |
| Front Wheel Quantity/Configuration            | 2/Rigid       |

4 additional technical attributes are available on the live Vestil product page.

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA