

Polyphenylene Sulfide Manual Rotary Drum Pump 10 In. x 8 In. x 12 In. Yellow

MODEL RP-90R

Drum Handling Equipment / Rotary Drum Pumps

PRODUCT OVERVIEW

The manual drum pump is designed for dispensing and transferring liquids out of fifty-five (55) gallon drum. It is ideal for transferring soluble, corrosive, volatile and aggressive chemicals (esters, alcohols, alkali, acids, hydrocarbons, petroleum based fluid, transmission fluid and water based chemicals).

KEY FEATURES

- Manual drum pump design dispenses and transfers liquids out of fifty-five gallon drums
- Ideal for transferring soluble, corrosive, volatile and aggressive chemicals for ideal operation
- Features durable construction for added strength and long life
- Use in industrial applications for optimal results

CORE PRODUCT DATA

ASSEMBLED WEIGHT
5 lbs

ASSEMBLED SIZE
8.625" W x 12.625" L x 52.125" H

SHIP WEIGHT
6 lbs

PACKAGE 1 SIZE
7" W x 25" D x 7" H

COLOR / FINISH
Yellow

FREIGHT TYPE
Parcel

AVAILABILITY Out of Stock - Please Contact Sales

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Pump Type	Rotary - Vane
Flow Dispense Per Stroke (ml)	300
Maximum Fluid Temperature Degrees (Fahrenheit)	140 Degrees Fahrenheit / 60 Degrees Celsius
MNPT Bung Size (in.)	2
Suction Tube Length Maximum (in.)	42
Inlet Outside Diameter (in.)	1-1/4
Outlet Curved Spot Outside Diameter (in.)	1
Maximum Viscosity (SSU)	2000
Seal Construction	PTFE
Vane Construction	PPS (Polyphenylene sulfide)
Suction Tube Construction	Polypropylene
Adjustable Outlet Degrees	0 - 360
Application Liquids	acid, alkali, gasoline, diesel, machine oil, water, alcohol, thinner and other chemical liquids
Component Materials	PPS, PTFE
Nitric Acid Resistance Percentage	40
Displacement per Stroke (ounces)	10.14
Pump Motor Type	Crank
Pump Mounting	Bung
Self-Priming	Yes
Outer Dimension of End Connection on Discharge	3/4
Inner Dimension of End Connection on Discharge	1

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=869>