

# Steel Counter Balanced Powered Drive Lift 2 In. to 118 In. Raised Height 2,000 Lb. Capacity Black / Yellow

**MODEL S-2CB-118**

Ergonomic Solutions / Counter-Balanced Powered Drive Lifts

## PRODUCT OVERVIEW

Counter balance design is ideal for die loading, machine feeding, and for loading and unloading trucks. High torque drive and lift motor handles heavy-duty jobs. Ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. Includes an electromagnetic disc brake with automatic dead-man feature that activates when the user releases the handle. Powered lift also includes batteries, an integral battery charger, and battery level gauge. Adjustable forks suitable for different pallets. A high level of serviceability simplifies maintenance and prolongs equipment life. Easy access battery compartment simplifies battery mai...

## KEY FEATURES

- Simple controls for quick movement
- Walk behind style for ergonomic posture
- Ability to raise to high levels of workspace
- Poly-on-steel steer and load wheels

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**2654 lbs**

**ASSEMBLED SIZE**  
**35.5" W x 110" L x 78" H**

**SHIP WEIGHT**  
**2652 lbs**

**PACKAGE 1 SIZE**  
**36" W x 101" D x 82" H**

**COLOR / FINISH**  
**Black / Yellow**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                             |                                       |
|---------------------------------------------|---------------------------------------|
| Uniform Capacity at 0 - 62" (lb.)           | 2,000                                 |
| Uniform Capacity at 62 - 118" (lb.)         | 1,000                                 |
| Service Range (in.)                         | 2 to 118                              |
| Fork Width/Length (in.)                     | 4 x 36-1/4                            |
| Adjustable Fork Spacing (in.)               | 8-3/8 to 23-1/4                       |
| Drive Motor                                 | 24V / 1 KW                            |
| Lift Motor                                  | 24V / 2 KW                            |
| Battery                                     | (2) 12V / 135 Ah                      |
| Battery Charger                             | 24V / 12 amp                          |
| Operation Time with Constant Use (hrs.)     | 3 to 4                                |
| Operation Time with Intermittent Use (hrs.) | 8                                     |
| Travel Speed - Unloaded (MPH)               | 3.43                                  |
| Travel Speed - Loaded (MPH)                 | 2.8                                   |
| Platform Ground Clearance (in.)             | 1-1/2                                 |
| Load Center (in.)                           | 19                                    |
| Mast Style                                  | Telescopic                            |
| Lift Speed w/o Load                         | 5.9" / sec                            |
| Lift Speed w/ Load                          | 2.95" / sec                           |
| Lower Speed w/o Load                        | 4" / sec                              |
| Lower Speed w/ Load                         | 3.15" / sec                           |
| Battery Depth                               | 14                                    |
| Battery Width                               | 14                                    |
| Battery Height                              | 10                                    |
| Battery Weight                              | 112                                   |
| Battery Freight Class                       | 70                                    |
| Battery NMFC Number                         | 60680                                 |
| Battery NMFC Description                    | UN2794 BATTERIES WET FILLED WITH ACID |
| Battery Subclass                            | 1                                     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=254>