

Steel/Plastic Hand Pump DC Powered Stacker with Adjustable Forks and Legs 118 In. Raised Height 2,000 Lb. Capacity Black / Yellow

MODEL SE/HP-118-AA

Ergonomic Solutions / Combination Hand Pump and Electric Stackers



PRODUCT OVERVIEW

An economical alternative DC powered lift stacker. Ideal for maintenance and commercial applications. This unit can be used as manual hand pump lift or electric powered lift. Ideal when power is not available. High quality hydraulic pump and DC lift system. Compact design and strong steel construction. An economical lift to handle tasks such as transporting dies, molds, and skids. Powered with two (2) 12V AGM batteries. Integral battery charger, battery level gauge, and adjustable lowering speed. All models are easily maneuverable using the standard pull handle. Forks measures 26." wide by 42" long. Individual forks are 6" wide.

KEY FEATURES

- Adjustable forks to fit multiple sizes
- Works well with pallets and skids
- Handle design makes portability convenient
- Ability for powered or manual lifting

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1095 lbs

ASSEMBLED SIZE
53" W x 67" L x 78" H

SHIP WEIGHT
1160 lbs

PACKAGE 1 SIZE
60" W x 64" D x 84" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity at 0 - 63" (lb.)	2,000
Uniform Capacity at 63 - 118" (lb.)	1,500
Fork Width/Length (in.)	4 x 42
Service Range (in.)	1-1/2 to 118
Adjustable Fork Spacing (in.)	8 to 26-3/4 (OD)
Adjustable Leg Spacing (in.)	40 to 50 (ID)
Overall Mast Height (in.)	72-3/4
Lift Motor	DC 24V / 1.3 KW
Battery	(2) 12V / 40 Ah
Battery Charger	24V / 10 amp
Raise Time w/ Load	1.67" / sec
Raise Time w/o Load	2.33" / sec
Lower Time w/ Load	4.76" / sec
Lower Time w/o Load	2.8" / sec
Battery Depth	8
Battery Width	14
Battery Height	8
Battery Weight	60
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=247>