

# Steel Hand Pump DC Powered Stacker with Fixed Forks and Legs 63 In. Raised Height 2,000 Lb. Capacity Black / Yellow

**MODEL SE/HP-63**

Ergonomic Solutions / Combination Hand Pump and Electric Stackers

## PRODUCT OVERVIEW

The combination hand pump and electric stacker is an economical alternative to the DC powered lift stacker. It's ideal for maintenance and commercial applications. This unit can be used as a manual hand pump lift or an electric powered lift, which is ideal when power is not available. It has a high quality hydraulic pump and DC lift system. The compact design and strong steel profile construction allows the lift to handle tasks such as transporting dies, molds, and skids. It features an integral battery charger, battery level gauge, and adjustable lowering speed. Easily maneuverable using a standard pull handle.

## KEY FEATURES

- Unique design features manual and powered forks
- Standard pull handle maneuvers easily
- Steel construction is ideal for maintenance and commercial applications
- High quality hydraulic pump and DC lift system conveniently lifts forks when loaded/unloaded

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**718 lbs**

**ASSEMBLED SIZE**  
**26.75" W x 65.375" L x 81.875" H**

**SHIP WEIGHT**  
**768 lbs**

**PACKAGE 1 SIZE**  
**41" W x 76" D x 83" H**

**COLOR / FINISH**  
**Yellow**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                        |                       |
|----------------------------------------|-----------------------|
| Uniform Capacity (lb.)                 | 2,000                 |
| Fixed Fork Spacing (in.)               | 26-3/4 (OD)           |
| Fork Width/Length (in.)                | 5-9/10 x 42           |
| Service Range (in.)                    | 3-3/8 to 63           |
| AGM Battery Quantity/Voltage/Amp Hours | (2) 12V               |
| Phase                                  | Single                |
| Hertz                                  | 60                    |
| Caster Material                        | Polyurethane          |
| Casters (qty.)                         | 4                     |
| Front Caster Diameter (in.)            | 4                     |
| Rear Caster Diameter (in.)             | 6-1/2                 |
| Width Between Forks (in.)              | 17                    |
| Leg Width (in.)                        | 24                    |
| Horsepower (HP)                        | 2                     |
| Maximum Wattage (watts)                | 1500                  |
| Maximum Ampere (amp.)                  | 120                   |
| Turning Radius (in.)                   | 51                    |
| Battery Depth                          | 8                     |
| Battery Width                          | 14                    |
| Battery Height                         | 8                     |
| Battery Weight                         | 60                    |
| Battery Freight Class                  | 60                    |
| Battery NMFC Number                    | 60700                 |
| Battery NMFC Description               | Gel batteries on unit |
| Lithium Battery Configuration          | C -- Contained In     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=247>